



KLIME-EZEE  
KNOCK DOWN RANGE | KK  
SWL 300 Kg



An Ideal product for buildings with limited entrance space, tight doorways / halls, low hanging lights and beams which make access restrictive.

- **Platform height** between 1250 - 4000 mm
- **Tread size** 550 (W) x 200 (D) mm
- **Platform Size** 550 (W) x 400 (D) mm

This range comes in knock-down form and must be assembled prior to use.

## KNOCK DOWN RANGE

### *Dimensions*

Product Code	Treads	Working Platform Height	Working Height	Overall Height	Overall Width	Overall Length	Packed Dims H x W x L	Weight	Brake Type
KK 05	5	1250	2250 - 3000	2250	850	1270	900 x 850 x 2450	55	Central brake
KK 06	6	1500	2500 - 3250	2500	850	1360	900 x 850 x 2700	62	Central brake
KK 07	7	1750	2750 - 3500	2750	850	1450	900 x 850 x 3000	70	Central brake
KK 08	8	2000	3000 - 3750	3000	850	1575	900 x 850 x 3400	78	Central brake
KK 09	9	2250	3250 - 4000	3250	850	1730	900 x 850 x 3600	90	Central brake
KK 10	10	2500	3500 - 4250	3500	1000	1905	900 x 1000 x 4000	98	Central brake
KK 11	11	2750	3750 - 4500	3750	1000	2070	900 x 1000 x 4400	105	Central brake
KK 12	12	3000	4000 - 4750	4000	1000	2230	900 x 1000 x 4700	116	Central brake
KK 13	13	3250	4250 - 5000	4250	1230	2470	900 x 1230 x 5000	125	Central brake
KK 14	14	3500	4500 - 5250	4500	1230	2630	900 x 1230 x 5200	130	Central brake
KK 15	15	3750	4750 - 5500	4750	1320	2795	900 x 1320 x 5500	138	Central brake
KK 16*	16	4000	5000 - 5750	5000	1320	2975	900 x 1320 x 5800	146	Central brake

**Please Note :** All dimensions are approximate and shown in mm, with weights shown in Kg.

Due to our ever-improving environment, we may make enhancements to our products which effect dimensions. Therefore reserve the right to amend these at any time to better serve our customer. Confirm the spec at [klime-ezee.com/kk](http://klime-ezee.com/kk).